



PC board type



Plug-in type



TM type

mm inch

RoHS Directive compatibility information  
<http://www.nais-e.com/>

## FEATURES

- **High inrush current capability**  
 1 Form A: 163 A inrush (TV-8)  
 2 Form A: 111 A inrush (TV-5)
- **High dielectric withstanding for transient protection:**  
 JC can withstand 10,000 V surge in  $\mu$ s between coil and contact.
- **Electrical life:**  
 1 Form A:  $10^5$  ope. at 15 A 250 V AC resistive load  
 2 Form A:  $10^5$  ope. at 10 A 250 V AC resistive load
- **UL/CSA, VDE, TÜV, SEMKO also approved.**

### About Cd-free contacts

We have introduced Cadmium free type products to reduce Environmental Hazardous Substances.  
 (The suffix "F" should be added to the part number)  
 Please replace parts containing Cadmium with Cadmium-free products and evaluate them with your actual application before use because the life of a relay depends on the contact material and load.

## SPECIFICATIONS

### Contact

Arrangement	1 Form A	2 Form A		
Initial contact resistance, max. (By voltage drop 6 V DC 1 A)	100 m $\Omega$			
Contact material	AgSnO <sub>2</sub> type			
Rating (resistive load)	Maximum switching power	3,750 VA	2,500 VA	
	Maximum switching voltage	250 V AC	250 V AC	
	Max. switching current	15 A	10 A	
	Min. switching capacity <sup>#1</sup> (Reference value)	100 mA, 5 V DC		
Expected life (min. operation)	Mechanical	$5 \times 10^6$		
	Electrical (resistive)	15 A 250 V AC	$10^5$	—
		10 A 250 V AC	—	$10^5$

### Coil

Nominal operating power	900 mW	1,000 mW
-------------------------	--------	----------

<sup>#1</sup> This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load.

### Remarks

- \* Specifications will vary with foreign standards certification ratings.
- <sup>#1</sup> Measurement of same location as "Initial breakdown voltage" section
- <sup>#2</sup> Detection current: 10mA
- <sup>#3</sup> Excluding contact bounce time
- <sup>#4</sup> Half-wave pulse of sine wave: 11ms; detection time: 10 $\mu$ s
- <sup>#5</sup> Half-wave pulse of sine wave: 6ms
- <sup>#6</sup> Detection time: 10 $\mu$ s
- <sup>#7</sup> Refer to 6. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT

### Characteristics

Maximum operating speed	20 cpm.	
Initial insulation resistance <sup>*1</sup>	Min. 100 M $\Omega$ at 500 V DC	
Initial breakdown voltage <sup>*2</sup>	Between open contacts	2,000 V rms for 1 min.
	Between contacts sets	2,000 Vrms for 1 min.
	Between contacts and coil	4,000 Vrms for 1 min.
Operate time <sup>*3</sup> (at nominal voltage)	Max. 30 ms	
Release time(without diode) <sup>*3</sup> (at nominal voltage)	Max. 10 ms	
Temperature rise (at nominal voltage)	Max. 55°C	
Shock resistance	Functional <sup>*4</sup>	196 m/s <sup>2</sup> {20 G}
	Destructive <sup>*5</sup>	980 m/s <sup>2</sup> {100 G}
Vibration resistance	Functional <sup>*6</sup>	10 to 55 Hz at double amplitude of 1.6 mm
	Destructive	10 to 55 Hz at double amplitude of 2 mm
Conditions for operation, transport and storage <sup>*7</sup> (Not freezing and condensing at low temperature)	Ambient temp.	-50°C to +60°C -58°F to +140°F
	Humidity	5 to 85%R.H.
Unit weight	Approx. 31 g 1.09 oz	

# TYPICAL APPLICATIONS

- Automatic garage door openers
- Microwave ovens
- Dryers
- Vending machines
- Copiers
- Air conditioners
- Stereo equipment
- TV sets

# ORDERING INFORMATION

Ex. JC 1a F — TM — DC12V — F

Contact arrangement	Mounting classification	Coil voltage	Contact material
1a: 1 Form A 2a: 2 Form A	Nil: PC board terminal S: Plug-in terminal TM: Top mounting	DC 6, 12, 24, 48 V	F: AgSnO <sub>2</sub> type

- (Notes) 1. TV rated types available 1 Form A: TV-8; 2 Form A: TV-5.  
 2. Standard packing. Carton: 50 pcs.; Case: 200 pcs.  
 3. UL/CSA, VDE, TÜV, and SEMKO certified products can also be supported. Please consult us.  
 4. Please inquire about the previous products (Cadmium containing parts).


# COIL DATA (at 20°C 68°F)

Contact arrangement	Nominal voltage. V DC	Pick-up voltage. V DC (max.)	Drop-out voltage. V DC (min.)	Coil resistance, Ω(±10%)	Nominal operating current, mA	Nominal operating power, W	Maximum allowable voltage, V DC (at 60°C)
1 Form A	6	4.8	0.6	40	150	0.9	6.6
	12	9.6	1.2	160	75	0.9	13.2
	24	19.2	2.4	640	37.5	0.9	26.4
	48	38.4	4.8	2,560	18.8	0.9	52.8
2 Form A	6	4.8	0.6	36	166.6	1.0	6.6
	12	9.6	1.2	144	83.3	1.0	13.2
	24	19.2	2.4	576	41.6	1.0	26.4
	48	38.4	4.8	2,300	20.8	1.0	52.8


# DIMENSIONS

mm inch


## PC board type JC1a




## Schematic




## PC board pattern (Bottom view)




## PC board type JC2a



## Schematic




## PC board pattern (Bottom view)




General tolerance: ±0.3 ±0.12

Tolerance: ±0.1 ±0.04

Top mount type



Plug-in type




General tolerance:  $\pm 0.3 \pm 0.012$


REFERENCE DATA

JC1a type


1. Maximum value for switching capacity



2.-(1) Coil temperature rise  
Point measured: Inside the coil  
Ambient temperature: 26°C 79°F




2.-(2) Coil temperature rise  
Point measured: Inside the coil  
Ambient temperature: 40°C 104°F




2.-(3) Coil temperature rise

Point measured: Inside the coil  
Ambient temperature: 60°C 140°F




3. Operate / release time




JC2a type

1. Maximum value for switching capacity




2.-(1) Coil temperature rise

Point measured: Inside the coil  
Ambient temperature: 26°C 79°F




2.-(2) Coil temperature rise

Point measured: Inside the coil  
Ambient temperature: 40°C 104°F




2.-(3) Coil temperature rise

Point measured: Inside the coil  
Ambient temperature: 60°C 140°F



3. Operate / release time



**ACCESSORIES**



JC1-SS



JC2-SS



JC1-PS








JC2-PS

JC2-SS



JC2-PS

mm inch

Tolerance:  $\pm 0.5 \pm .020$




Panel cutout  
Tolerance:  $\pm 0.1 \pm .004$



JC1-PS

PC board Pattern



JC2-PS

Tolerance:  $\pm 0.1 \pm .004$

(Note)

Outward dimensions and chassis cutout dimensions for JC1-SS and JC1-PS are same as those of JC2-SS and JC2-PS respectively.  
UL/CSA approved type is standard.

**For Cautions for Use, see Relay Technical Information**